

TECHNICAL DATA SHEET

HARNESS RIO

EX200-UNI



Product Description :

Fall arrest harness 2 points

- 1 back D-ring for dorsal fall arrest attachment
- 2 web loops to be linked together to form the front fall arrest attachment point

Lightweight and quick to don.

Adjustable chest and leg straps.

Unique size.

Certified to EN361

Technical information :

Webbing	Polyester, width 45mm, Breaking tenacity >0.6N/tex
Sewing threads	Polyester 500D, Breaking tenacity >0.6N/tex
Back plate	Dorsal plastic plate for D-ring with A marking for the back D-ring Material : Injection Molding
D-rings (back)	Material : Steel, protected by a black electrophoretic paint
Chest strap webbing	Polyester, width 25mm, Breaking tenacity >0.6N/tex
Chest strap buckle	Type : Quick connect, Material : Injection Molding
Leg strap buckles	Type : pass-through, Material : Steel, protected by a black electrophoretic paint
Elastic ring	Material : Elastic rubber band, Polyester, Width: 25mm
Weight	0.8 kgs
Certification	EN361:2002

REGULATION OF March 19, 1993

PPE against falls from height are classified in category III (fatal risks):
"[t]his personal protective equipment must have been subject, for less than twelve months at the time of its use, to the periodic general inspection provided for in Article R.233-42-2 of the [French] Labor Code"

For any information, please contact our team at
+33 (0)5.45.78.83.85

EXYAN
FALL PROTECTION EXPERT