

FALL ARREST LANYARD FIDJI



Certified to EN355

Product Description :

Rope fall arrest lanyard equipped with energy absorber to stop a fall and reduce the impact of a fall to maximum 6kN.

Flexible and resistant :

- Tested to 140kgs
- Made of kernmantel rope
- Absorber protected by a textile housing openable through a zipper
- Safety stitchings protected by transparent shell

Exists in different lengths and versions of connectors / hooks

Reference	Length	Connector – Harness side	Connector – Anchor side	Product Weight
EX600-150	1.5m	Alu Twistlock	Alu Twistlock	580gr
EX600-200	2m	Alu Twistlock	Alu Twistlock	620gr
EX601-150	1.5m	Alu Twistlock	Alu Scafhook	760gr
EX601-200	2m	Alu Twistlock	Alu Scafhook	800gr

For other versions, please consult us.

Technical information :

Rope	Polyamide & Polyester braided rope, diameter 11mm
Sewing threads	Polyester 500D, Breaking tenacity >0.6N/tex
Energy absorber	Polyester webbing, width 45mm
Energy absorber cover	Wear resistant polyester housing with zipper
Protective shell	Plastic transparent cover
Connection to the harness	Aluminum twistlock carabiner, opening 19mm, certified to EN362 class B
Connection to the anchor	Aluminum twistlock carabiner, opening 19mm, certified to EN362 class B Or Aluminum scafhook, opening 56mm, certified to EN362 class A
Length	Available in 1.5m and 2m
Max user weight	140kgs
Certification	EN355:2002

REGULATION OF March 19, 1993

PPE against falls from height are classified in category III (fatal risks):
 "[t]his personal protective equipment must have been subject, for less than twelve months
 at the time of its use, to the periodic general inspection provided for
 in Article R.233-42-2 of the [French] Labor Code"
 For any information, please contact our team at
 +33 (0)5.45.78.83.85

EXYAN
 FALL PROTECTION EXPERT