

ENERGY ABSORBER WITH LANYARD HAVANA



Product Description :

Fall arrest lanyard in stretch webbing equipped with energy absorber to stop a fall and reduce the impact of the fall to 6kN.

Light and easy to handle.

Minimizes the risk of tripping thanks to its stretch webbing.

Flexible and resistant:

- Tested to 140kgs
- Absorber protected by a textile housing openable through a zipper

Exist in other versions of connectors / hooks

Certified to EN355

Reference	Length	Connector - Harness side	Connector - Anchor side	Product Weight
EX630-185	1.85m	Alu Twistlock	Alu Twistlock	550 gr
EX631-185	1.85m	Alu Twistlock	Alu Scafhook	740 gr

For other versions, please consult us.

Technical information :

Webbing	Polyester webbing, width 27mm
Sewing threads	Polyester 500D, Breaking tenacity >0.6N/tex
Energy absorber	Polyester webbing, width 45mm
Energy absorber cover	Wear resistant polyester housing with zipper
Connection to the harness	Aluminum twistlock carabiner, opening 19mm, certified to EN362 class B
Connection to the anchor	Aluminum scafhook, opening 56mm, certified to EN362 class A
Length	Available in 1.85m (total length, lanyard fully extended)
Max user weight	140kgs
Certification	EN355:2002

REGULATION OF March 19, 1993

PPE against falls from height are classified in category III (fatal risks):
 "[t]his personal protective equipment must have been subject, for less than twelve months
 at the time of its use, to the periodic general inspection provided for
 in Article R.233-42-2 of the [French] Labor Code"

For any information, please contact our team at
 +33 (0)5.45.78.83.85

EXYAN
FALL PROTECTION EXPERT