

# TECHNICAL DATA SHEET

## LANYARD RHODES



### Product Description :

Lanyard in kernmantel rope

This lanyard is not a fall arrester but a movement limiter if used as such : it prevents a fall if positioned at a sufficient distance from the edge.

It can be used in conjunction with our energy absorber to be used as a fall arrest lanyard.

Exists in different versions :

Reference	Length	Connector – Harness side	Connector – Anchor side	Product Weight
EX650-100	1m	Steel Twistlock	Steel Twistlock	0.62kgs
EX650-150	1.5m	Steel Twistlock	Steel Twistlock	0.95kgs
EX651-150	1.5m	Steel Twistlock	Steel Scafhook	1.27 kgs

**Certified to EN354**

### Technical information :

Rope	Polyamide & Polyester braided rope, diameter 11mm
Sewing threads	Polyester 500D, Breaking tenacity >0.6N/tex
Stitching Protection	Plastic transparent shrink tube
Connection to the harness	Aluminum twistlock carabiner, opening 19mm, certified to EN362 class B
Connection to the anchor	Aluminum twistlock carabiner, opening 19mm, certified to EN362 class B Or Steel scafhook, opening 55mm, certified to EN362 class A
Length	Available in 1m and 1.5m
Certification	EN354:2010

#### REGULATION OF March 19, 1993

PPE against falls from height are classified in category III (fatal risks):  
 "[t]his personal protective equipment must have been subject, for less than twelve months  
 at the time of its use, to the periodic general inspection provided for  
 in Article R.233-42-2 of the [French] Labor Code"

For any information, please contact our team at  
 +33 (0)5.45.78.83.85

**EXYAN**  
 FALL PROTECTION EXPERT