

TECHNICAL DATA SHEET

VERTICAL TEMPORARY LIFELINE CANCEL



Product Description :

Temporary vertical rope lifeline with mobile fall arrester

Flexible and easy to use :

- Follow the user movement and stop the fall immediately
- Equipped with a twistlock carabiner

Resistant :

- Steel rope grab on polyester rope

Safety :

- Non removable from the rope (no risk of wrong installation of the device)

Certified to EN353-2

Exists in different lengths :

Reference	Length	Product Weight
EX700-10	10m	1.6 kgs
EX700-20	20m	2.5 kgs
EX700-30	30m	3.4 kgs

Technical information :

Rope	Polyamide braided rope, diameter 12mm,
Sewing threads	Polyester 500D, Breaking tenacity >0.6N/tex
Protective shell	Plastic rigid cover, transparent to allow easy inspection
Mobile fall arrester	Rope Grab, Material : Steel
Energy Absorber	Webbing, width 45mm, protected by shrink tube
Carabiner	Steel twistlock carabiner, opening 20mm
Rope Termination (Top)	Rope sewn buckle, protected by rigid plastic transparent shell
Rope Termination (Bottom)	Rope sewn buckle, protected by transparent shrink tube
Max user weight	140kgs
Certification	EN353-2:2002

REGULATION OF March 19, 1993

PPE against falls from height are classified in category III (fatal risks):
"[t]his personal protective equipment must have been subject, for less than twelve months
at the time of its use, to the periodic general inspection provided for
in Article R.233-42-2 of the [French] Labor Code"

For any information, please contact our team at
+33 (0)5.45.78.83.85

EXYAN
FALL PROTECTION EXPERT