

## TECHNICAL DATA SHEET

# WEBBING EXTENSION

EX900-01



### Product Description :

Extension lanyard

**Efficient and easy to use :**

- Designed to be used on a harness fall arrest attachment point for greater easiness to connect to the fall arrest system.
- Provides freedom of movements
- Equipped with a Velcro to attach the extreme end on the shoulder strap of the harness and keep it therefore accessible at any time for connection or disconnection

**Versatile : 2 connection possibilities**

- With lark's head knot around the D-ring
- Or Directly to the back D-ring with a carabiner

**Certified to EN354**



Direct connection :

- Length +/-40cm (without connector)



Lark's head knot :

- Length +/-35cm (without connector)

### Technical information :

Webbing	Polyester, width 45mm, Breaking tenacity >0.6N/tex
Sewing threads	Polyester 500D, Breaking tenacity >0.6N/tex
Termination 1	Sewn loop for connection to the harness D-ring
Termination 2	Webbing sewn loop for connection to the fall arrester, Velcro to keep it accessible on the shoulder strap
Certification	EN354:2010

#### REGULATION OF March 19, 1993

PPE against falls from height are classified in category III (fatal risks):  
"[t]his personal protective equipment must have been subject, for less than twelve months at the time of its use, to the periodic general inspection provided for in Article R.233-42-2 of the [French] Labor Code"

For any information, please contact our team at  
+33 (0)5.45.78.83.85

**EXYAN**  
FALL PROTECTION EXPERT