#### TECHNICAL DATA SHEET

# ENERGY ABSORBER WITH DOUBLE LANYARD FIDJI Y

Ref EX620-200 : 2m Ref EX620-150 : 1.5M





### **Product Description:**

Twin Fall arrest lanyard equipped with energy absorber to stop the fall and reduce the impact of the fall to under 6kN.

Thanks to its double leg, it allows movement and cross over obstacles while one leg remains connected.

Flexible and resistant:

- Tested to 140kgs
- Made of kernmantel rope
- Absorber protected by a textile housing openable through a zipper
- Safety stitchings protected by transparent shell
- Equipped with a twistlock carabiner and 2 aluminum scafhooks.

## **Certified to EN355**

For other versions, please consult us.

#### **Technical information:**

Rope	Polyamide & Polyester braided rope, diameter 11mm
Sewing threads	Polyester 500D, Breaking tenacity >0.6N/tex
Energy absorber	Polyester webbing, width 45mm
Energy absorber cover	Wear resistant polyester housing with zipper
Protective shell	Plastic transparent cover
Connection to the harness	Aluminum twistlock carabiner, opening 19mm, certified to EN362 class B
Connection to the anchor	Aluminum scafhook, opening 56mm, certified to EN362 class A
Length	Available in 1.5 and 2m
Product weight	1.23 kgs
Max user weight	140kgs
Certification	EN355:2002

#### **REGULATION OF March 19. 1993**

PPE against falls from height are classified in category III (fatal risks):

"[t]his personal protective equipment must have been subject, for less than twelve months
at the time of its use, to the periodic general inspection provided for
in Article R.233-42-2 of the [French] Labor Code"

For any information, please contact our team at
+33 (0)5.45.78.83.85



