

TECHNICAL DATA SHEET

WIRE CABLE SELF RETRACTING LIFELINE 3M



Product Description :

Resistant

- Self retracting lifeline with stainless steel cable
- Housing highly resistant to shocks and friction
- Vertical use
- Conform for ATEX zone 1



II 2G Ex h IIC T6 Gb
II 2D Ex h IIIC T85°C Db

Easy to use

- Compact
- Equipped with two swivels (one at the top, one at the bottom of the device) to follow the user's movements with complete freedom and avoid the risk of the cable being twisted

Certified to EN360

Reference	Length	Product weight
EX300-03	3m	2.2 kgs

Technical information :

Wire cable	Stainless steel Ø4.5mm, Breaking strength >15kN
Housing	Polymer
Termination (Top)	Removable twistlock connector, mounted on a swivel
Termination (Bottom)	Non-removable twistlock connector with swivel and fall indicator
Temperature of use	Temperature range : -30°C to +50°C
Dimensions	184x115x74 mm
Use	Vertical use
Max user weight	137kgs
Certification	EN360:2002

REGULATION OF March 19, 1993

PPE against falls from height are classified in category III (fatal risks):
"[t]his personal protective equipment must have been subject, for less than twelve months at the time of its use, to the periodic general inspection provided for in Article R.233-42-2 of the [French] Labor Code"

For any information, please contact our team at
+33 (0)5.45.78.83.85

EXYAN
FALL PROTECTION EXPERT