

**TECHNICAL DATA SHEET**

# **WIRE CABLE SELF RETRACTING LIFELINE TOKYO EDGE**

**REF EX350**



**Product Description :**



**Certified to EN360**

**Resistant**

- Self retracting lifeline with galvanized steel cable
- Housing highly resistant to shocks and friction
- Edge tested for horizontal use

**Easy to use**

- Carrying Handle
- Equipped with two carabiners, each with a swivel (one at the top, one at the bottom of the device) to follow the user's movements with complete freedom and avoid the risk of the cable being twisted

**Length :** 6m (EX350-06),  
10m (EX350-10)  
15m (EX350-15)  
20m (EX350-20)

**Technical information :**

<b>Wire cable</b>	Galvanized steel, Breaking strength >15kN
<b>Housing</b>	Polymer
<b>Termination (Top)</b>	Removable twistlock connector, mounted on a swivel
<b>Termination (Bottom)</b>	Non-removable twistlock connector with swivel and fall indicator
<b>Space clearance</b>	Minimum 1.50m (stop the fall <50cm)
<b>Temperature of use</b>	Temperature range : -30°C to +50°C
<b>Use</b>	Tested for Horizontal use
<b>Max user weight</b>	140kgs
<b>Certification</b>	EN360:2002

**REGULATION OF March 19, 1993**

PPE against falls from height are classified in category III (fatal risks):  
"[t]his personal protective equipment must have been subject, for less than twelve months at the time of its use, to the periodic general inspection provided for in Article R.233-42-2 of the [French] Labor Code"  
For any information, please contact our team at  
+33 (0)5.45.78.83.85

**EXYAN**  
FALL PROTECTION EXPERT